


ISOMETRIC EXPLODED VIEW

CONCRETE PAD
6" THICK

COMPACTED
STONE

MANHOLE COVER & RING
SEE DETAILS C06.01 & C06.02

ISOMETRIC SECTION VIEW



CENTERLINE MH COVER THRU MH CASTING OPENING

PLACE 1/2" GROUT BETWEEN
MH FRAME RING AND CONCRETE
GRADE RING

4" CONCRETE GRADE RING
(MAXIMUM OF 24" FROM TOP
OF CASTING TO FIRST STEP)

PLACE 1/2" GROUT BETWEEN
CONCRETE GRADE RINGS

PLACE 1/2" GROUT BETWEEN
CONCRETE GRADE RING AND
MANHOLE CASTING

EXISTING MANHOLE CASTING

NOTE:
▲ INFI-SHIELD EXT. SEALING
SYSTEM ON ALL PRECAST
GRADE RING JOINTS
(DETAIL 532.11)

PRECAST
GRADE RINGS



TOWN of CLAYTON

USE WITH THE TOWN of CLAYTON STANDARD SPECIFICATIONS ONLY

**MANHOLE RING AND COVER
GRADE ADJUSTMENT**

SCALE: Not To Scale	DETAIL # 2 C06.03
REVISION DATE: July, 2010	SHEET #: 1 of 1